




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: B01J 19/00		A2	(11) International Publication Number: WO 00/16893
		(43) International Publication Date:	30 March 2000 (30.03.2000)
(21) International Application Number: PCT/GB99/03109		Published 3/3/2000 Not Annotated photocopy 12	
(22) International Filing Date: 17 September 1999 (17.09.1999)			
(30) Priority Data: 9820163.5 17 September 1998 (17.09.1998) GB			
(60) Parent Application or Grant SENTEC LIMITED [/]; (). DAMES, Andrew [/]; (). ENGLAND, James [/]; (). COLBY, Edward [/]; (). DAMES, Andrew [/]; (). ENGLAND, James [/]; (). COLBY, Edward [/]; ().			
(54) Title: BIO-ASSAY TECHNIQUE (54) Titre: TECHNIQUE DE BIODOSAGES /			
(57) Abstract <p>The present invention relates to a system for carrying out parallel bioassays. Micro-fabricated labels (7) are made to each carry a biochemical test, many different labels are mixed together with an analyte sample (8). A device that reads the individual labels isolates the results of the individual tests. The microfabricated labels have a surface layer of anodised metal and are produced by anodising, lithographic patterning and etching steps. Aluminum is the preferred metal.</p> <p>(57) Abrégé L'invention concerne un système pour effectuer des biodosages en parallèle. On crée par micro-usinage des étiquettes (7) dont chacune est destinée à accueillir un test biochimique, puis on mélange plusieurs étiquettes différentes avec un échantillon d'analyte (8). Un dispositif, qui lit les étiquettes individuelles isole les résultats des tests individuels. Les étiquettes créées par micro-usinage sont munies en surface d'une couche en métal anodisé fabriquée par anodisation, par dessin des motifs au moyen d'une technique lithographique et par gravure. On utilise de préférence l'aluminium.</p>			

class
427/118
→ 427
class 118

cp3



1762
1762
cp3

ET

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B01J 19/00		A2	(11) International Publication Number: WO 00/16893
			(43) International Publication Date: 30 March 2000 (30.03.00)
(21) International Application Number: PCT/GB99/03109			(81) Designated States: AU, CN, IN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(22) International Filing Date: 17 September 1999 (17.09.99)			
(30) Priority Data: 9820163.5 17 September 1998 (17.09.98) GB			
(71) Applicant (for all designated States except US): SENTEC LIMITED [GB/GB]; Patent Department, Terrington House, 13-15 Hills Road, Cambridge, Cambridgeshire CB2 1GE (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): DAMES, Andrew [GB/GB]; 74 de Freville Avenue, Cambridge, Cambridgeshire CB4 1HU (GB). ENGLAND, James [GB/GB]; 44A Butt Lane, Milton, Cambridge, Cambridgeshire CB4 6DG (GB). COLBY, Edward [GB/GB]; 45 Argyll Road, Cambridge, Cambridgeshire CB1 3LR (GB).			


Published

Without international search report and to be republished upon receipt of that report.

(54) Title: BIO-ASSAY TECHNIQUE

(57) Abstract

The present invention relates to a system for carrying out parallel bioassays. Micro-fabricated labels (7) are made to each carry a biochemical test, many different labels are mixed together with an analyte sample (8). A device that reads the individual labels isolates the results of the individual tests. The microfabricated labels have a surface layer of anodised metal and are produced by anodising, lithographic patterning and etching steps. Aluminum is the preferred metal.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Description

5

10

15

20

25

30

35

40

45

50

55

Bio-assay Technique

Field of the Invention

This invention relates to the field of micromachined or microfabricated coded substrates, particularly but not exclusively for use as a parallel bioassay technique.

Background

Massively parallel bioassay tests are the enabling techniques that have made the majority of recent advances in genetics, screening and drug discovery possible. Thousands or millions of tests that previously were carried out one by one may now be combined into a single experiment yielding thousands or millions of results. The key to this process has been the development of techniques that allow the results of the many different tests to be separated from each other.

A number of existing techniques are described below. The techniques consist of labelling each of the constituent experiments in a manner that can be read after the experiment has completed. Labels used at present include the position of the experiment on the surface of a test chip and the fluorescent spectrum of a particle to which the experiment is bound.

Affymetrix's GeneChip probe array is a DNA sequence testing chip, where tens of thousands of different DNA probes are located at known points on a large 2D array. The fabrication process is described in, for example US 5,744,305 or US 5,143,854. Standard DNA hybridisation techniques are used in a chamber above the chip, and the test results are read out optically by the positions of fluorescent dots on the array (see, for example, US 5,578,832). The combinations of tests are pre-determined during the manufacture of the chip.

Luminex Corporation's FlowMetrix system makes use of coded microspheres, 6.5 μ m in diameter. Each bead incorporates red and orange fluorophores to make up the code.

Eight different intensities are possible, allowing 64 different bead types. A green fluorescent marker is used for the probes. This system is described in US 5,736,330. The system has a relatively small number of codes, and requires complex, multi-wavelength optics on flow cytometers to read the codes and fluorescence of the test.

5 NanoGen has a semiconductor-based microchip array, APEX, which is aimed specifically
at DNA binding and sequencing experiments. NanoGen's chip is programmable by the
10 end user with different arrays of DNA probes (see, for example, US 5,605,662 and US
5,929,208).

15 There are a number of other particle or substrate-based assay techniques under the general
heading of Combinatorial Chemistry. For examples, WO 96/24061 describes a library of
tests using radio-frequency identification tags. WO 97/32892 describes a composite
10 support for use a combinatorial chemistry substrate. GB 2306,484 describes two-part
support particles for combinatorial chemistry.

Summary of the Invention

25 This invention describes a system for carrying out massively parallel multiple bioassay tests
in a low-cost, fast and convenient manner. The scheme involves making a suspension (an
assay) containing many thousands of different types of micro-machined coded labels,
(micro-labels), each code carrying a different biochemical test or probe.

30 An assay is constructed by mixing together suspensions of chosen sets of active micro-
labels. Assays are customised to particular applications, independently of the original
fabrication of the micro-labels.

35 The sample under test is marked with a fluorescent label and incubated with the assay.
Only micro-labels with probes that bind to the fluorescent sample molecules will become
25 fluorescent.

40 The micro-labels are fabricated from an anodisable material such as aluminium, initially
deposited onto a planar substrate with a soluble release layer. The metal surface is anodised
before patterning. This allows the attachment of a wide range of biochemically active
45 agents for use as highly selective probes.

50 Standard optical lithography and dry etching is used to pattern the aluminium into separate
micro-labels. The code is stored on the micro-labels as a series of holes using coding

schemes similar to those found on bar codes. The biochemical probes may be attached to the surface either before or after the lithography step. The micro-labels are then released into an aqueous suspension. Each different micro-label code has a unique probe associated with it. Micro-labels with up to 100,000 different variants have been demonstrated.

A flow-based reader system, similar to a flow cytometer, draws through thousands of micro-labels per second, reading both the bar code and the result of the test. The test result is measured by the degree of fluorescence. An alternative planar reading system, in which the micro-labels are plated out onto a flat substrate, uses fluorescence microscopy and image processing to read the results of the tests.

Brief Description of the Drawings

Embodiments of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 illustrates a single micro-label incorporating a transmission optical barcode, Figure 2 illustrates a parallel bio-assay comprising two binding event experiments, Figure 3 illustrates a wafer scale fabrication process for micro-labels, Figure 4 illustrates a porous structure resulting from anodic oxidation of an aluminium surface, Figure 5 illustrates a flow through micro-label reading device, Figure 6 illustrates the use of orthogonal interrogation beams to enable labels to be read regardless of rotation

Detailed Description

Micro-labels

Figure 1 shows a micro-label, 1, in the form of a micro-machined miniature optical bar code, made from aluminium. The bar code is formed by a series of holes, 2, in the aluminium.

Each micro-label of this type is about 100 μm long, 3, by 10 μm wide, 4, by 1 μm thick, 5, and is capable of storing up to 100,000 different codes. Around 10 million such micro-

optical bar
holes

> #7

100 μm

100 10 \times 1

1000²

5 labels can be fabricated on a single 6-inch diameter substrate. Different lengths of micro-label, from 40-100 μm , carrying between 2 and 5 decimal digits of data, have been
10 fabricated. Each different code is associated with a unique biochemical probe. Coding schemes such as those used in EAN and UPC bar codes are used, to provide strong error
15 checking when the codes are read.

Probes and Assays

15 With reference to Figure 2, an assay, 6, of micro-labels, is constructed by mixing together suspensions of chosen sets of active micro-labels. Each different code has a unique
20 biochemical probe associated with it, which binds to a specific type of molecule. Binding reactions may be selected from the group consisting of antibody-antigen, enzyme-substrate, enzyme-receptor, toxin-receptor, protein-protein and avidin-biotin.

25 The sample under test, 8, is marked with a fluorescent label and incubated with the assay.

15 Only micro-labels, 7, with probes that bind to the fluorescent sample molecules will become fluorescent, 10. The result of the test is measured by the degree of fluorescence of different types of micro-labels.

30 An example of an application of the present invention is the screening of serum for a selection of specific antibodies in a parallel bioassay. Antigens to the antibodies are used as
20 probes and bound to micro-labels marked to identify these antigens. The micro-labels are incubated with the sample and then incubated with an antibody specific fluorescent label.
35 The micro-labels are then passed through a reader that measures the degree of fluorescence of the labels and their identity. Correlation of the identities of the micro-labels with their
25 degree of fluorescence provides indication of the binding of antibodies in the sample with the surface bound antigens.
40

Micro-label Fabrication

45 The fabrication process for the micro-labels will now be described with reference to Figure
30 3.

Substrate

A substrate material, 11, such as a silicon wafer, is first coated with a soluble release layer, 12. In the preferred embodiment, this is a spin-coated layer of polymethyl methacrylate resist, baked at 150°C to drive off the solvents.

A layer of aluminium, 13, 1 μm thick, is deposited onto the substrate. This is achieved using a standard vacuum sputter coating technique, commonly used in semiconductor device fabrication.

The aluminium layer, 13, is anodised, 14, at a voltage of 30V in 4% phosphoric acid, using a pure aluminium cathode, for 30s, at a current density of 10 mA/cm². This leads to a 100 nm anodised layer, 15, with a pore size of around 40 nm.

At this stage (depending on the application) the aluminium surface may be coated with probe molecules, 16, by immersing the surface in an aqueous solution/suspension of the molecules.

The substrate is spin-coated with conventional optical resist, 17, Shipley S1813. The label pattern, 18, is exposed using a hard-contact optical mask, and developed using aqueous alkaline developer (MF319). The pattern is transferred into the aluminium layer using reactive ion etching with SiCl₄.

If the probe attachment is to be carried out after the lithography, the optical resist, 17, may be removed at this stage using a solvent such as isopropyl alcohol. This leaves the release layer, 13, intact, with the patterned aluminium layer, 20, on top. The probe molecules, 16, may then be attached as described above, whilst the micro-labels are still attached to the substrate.

The micro-labels with attached probes are released, 21, from the substrate using a solvent such as acetone. Dilution and filtration leaves the micro-labels, 22, in an aqueous suspension ready for combination into an assay.

5 The fabrication process is suitable for a wide variety of shapes of micro-labels with holes in, including both the substantially linear type of Figure 1 and other forms of square, rectangular and round micro-labels.

5 Anodisation and Surface Chemistry

10 Proteins bind only weakly with an untreated aluminium surface when incubated in an aqueous solution. By modifying the surface this binding can be selectively enhanced to control when the binding occurs. This is important because it allows the probe molecules to be bound strongly to the surface at time of manufacture whilst maintaining weak non-specific binding of the fluorescent target molecules during the test. In this way the discrimination of the test is maximised.

15 There exists a very wide body of knowledge, gained in the first half of this century, on surface protection of aluminium components through the use of electrochemical processes.

20 Methods for growing porous surfaces are well known, as are processes for sealing these surfaces. We have exploited this knowledge to develop a relatively simple process that grows an adsorbing surface with well controlled porosity and depth. This surface binds the chosen proteins well soon after treatment, but heals with time to prevent further binding.

25 In order to generate the appropriate anodised surface morphology, it is necessary to understand the structure of typical of biomolecules used as probes. Cryogenic atomic-force-microscopy allows direct imaging of such biomolecules. For example, Immunoglobulin-G (IgG) has a Y-shaped structure. The size of the IgG molecule is approximately 40nm across, which can be considered to be a typical size.

30 With reference to Figure 4, during anodisation, an aluminium oxide layer, 23, grows on the surface of the aluminium. This oxide layer grows in a two dimensional hexagonal cell structure, 24, the size of each cell depending on the electrochemical forming voltage. In the centre of each cell, a pore, 25, forms with an aperture smaller than the width of the cell, 26. As the anodisation process progresses, the thickness, 27, of the oxide layer and the depth of the pores, 28, increase, but the cell width, 26, and the pore aperture, 28, remains constant.

Reading Systems

Two classes of reading system have been developed. These are based on flow cells, and on planar imaging of plated-out micro-labels.

The flow-cell reader, shown schematically in Figure 5, utilises a design that induces the micro-labels, 1, to flow down the centre of a tube, 29 through a defined reading zone, 30. Normally, elongated particles in flow would have a tendency to tumble. However, by using an accelerating sheath fluid, 31, and injecting the micro-labels into the centre of this flow, 32, a hydrodynamic focussing effect is achieved that causes all the micro-labels to align, and pass through a well-defined focal point, 30, somewhere downstream of the injection point, 32.

At the hydrodynamic focal point, 30, two orthogonal focused beams, 33, 34, of laser light from a 488 nm argon-ion laser interrogate the micro-labels. This is detailed in Figure 6.

The use of two orthogonal interrogation beams enables the interrogation of micro-labels, regardless of their rotation with respect to the frame of reference of the flow tube. The label, 1, in Figure 6, is shown at an angle of 45° to both incident beams, which is the worst possible case. The geometry of the micro-labels, shown in Figure 1, means that light is still transmitted through the holes in the label, 2. The holes modulate the transmitted intensity at the detector, 35, as the label passes through, generating a serial stream of information that is analysed in the same way as a conventional bar code. Simultaneously, the degree of fluorescence is measured, using an epi-fluorescence detector, 36. This is correlated with the code on the label. High numerical-aperture optics (microscope objective lenses) are used to achieve the desired resolution. The optimal flow-cell design has flat walls, to avoid the use of custom cylindrical imaging elements.

Once sufficient micro-labels have been read the reader calculates the results of all the tests. This number required is typically between 10 and 100 copies of each type of micro-label, to enable statistical analysis to be used. The test results show the mean and standard deviation of the fluorescence for each type of probe.

In a planar reading system, the micro-labels are plated out onto a flat substrate. This is either a filter substrate, or a transparent substrate. Conventional fluorescence microscopy

is used to analyse the plated substrate systematically. An image-processing system captures pictures of each field of the substrate. Transmitted light is analysed separately from fluorescent light. Each micro-label is identified from its transmitted light profile, and the fluorescence signal integrated over the surface of the label is recorded. Once again, between 10 and 100 of each type of micro-label are required to give a good statistical analysis.

Applications

A typical application uses a suspension of probes for a number of different antibodies (e.g. hepatitis, HIV). A reading system takes a drop of blood from a patient, labels it with fluorescent marker, and incubates it with the probe suspension for a few minutes. The suspension is fed through a microfluidic detector system.

Further Embodiments

Micro-label designs for planar reading systems are not limited to the linear designs described above, which are primarily intended for flow-through reading systems. Planar systems can use 2D patterns, fabricated on labels which are closer to being square or rectangular, rather than linear. Coding schemes similar to conventional 2D barcodes are then used. The outline of the label also gives information, particularly about orientation.

Labels incorporating magnetic material can use magnetic separation. This is useful if the sample being tested contains solid matter of similar size to the labels that could contaminate the results.

Micro-labels can be fabricated using any substrate that can be coated with an anodisable metal such as aluminium. This is particularly attractive when a mass-production method such as embossing of an aluminium-coated plastic is used to fabricate the micro-labels.

Claims

5

10

15

20

25

30

35

40

45

50

55

Claims

1. A solid support for biochemical (binding experiment) assays with an anodised metal surface layer
2. A support according to claim 1 wherein the metal surface layer is aluminium
3. A support according to claim 1, with a modification to enhance the affinity of the reagents of said binding experiments
4. A method of fabricating supports according to claim 1, comprising sputter coating of a flat surface with the metal comprising the support, lithographic patterning of the metal, and etching of the metal to leave individual supports
5. A method according to claim 4, whereby the said surface consists of a layer of soluble material on a rigid support, thereby allowing the supports to be released by solvation of the soluble material
6. A method according to claim 5 whereby the soluble material is a resist
7. A support according to claim 2, whereby the modification results in a porous surface
8. A support according to claim 7, whereby the pore size is approximately matched to the size of the biochemically active molecules to be bound
9. A method of fabricating the support according to claim 3, wherein said modification is by electrochemical means
10. A method according to claim 9, wherein said modification is by anodic oxidation of the support surface
11. A method according to claim 10, wherein said anodisation is carried out at a voltage of up to 150 V

12. A method according to claim 11 whereby said anodisation is carried out at a voltage from 4 V to 30 V

13. A support according to claim 1, wherein said support is preferentially smaller than 100 µm in length by 100 µm in width by 100 µm in thickness

< 100 µm (L)
100 µm W

14. A support according to claim 1, incorporating a spatially varying pattern for identification purposes

15. An optical reader for reading the patterns and identifying the supports according to claim 14

16. Supports according to claim 14, wherein said pattern is a barcode

17. Supports according to claim 16, wherein said barcode is a linear barcode

barcode

18. A reader according to claim 15 operating by means of transmission optics

optics

19. A reader according to claim 18 wherein said supports are transported through an optical read volume by a fluidic system

20. A process whereby the results of many binding experiments are separated from one another according to the identities of substrates according to claim 14 to which one member of said binding pair is attached, as determined by a reader according to claim 15.

21. A process according to claim 20 wherein said binding pairs are selected from the group consisting of antibody-antigen, enzyme-substrate, enzyme-receptor, toxin-receptor, protein-protein and avidin-biotin

Antibody

22. A process according to claim 20, wherein the attached member of said binding pair is fluorescently labelled

B

5

23. A support according to claim 14 in which the pattern comprises a series of holes in the support

10

24. A reader according to claim 18 in which there are two substantially orthogonal light transmission paths

15

25. A reader according to claim 24 incorporating one or more fluorescence detectors

20

25

30

35

40

45

50

55

FIGURES




Figure 1




Figure 2

2/4




Figure 3




Figure 6

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification: B01J 19/00, C25D 11/04, G01N 33/53, G06K 19/06	A3	(11) International Publication Number: WO 00/16893 (43) International Publication Date: 30 March 2000 (30.03.2000)
(21) International Application Number: PCT/GB99/03109 (22) International Filing Date: 17 September 1999 (17.09.1999) (30) Priority Data: 9820163.5 17 September 1998 (17.09.1998) GB (60) Parent Application or Grant SENTEC LIMITED [/]; (). DAMES, Andrew [/]; (). ENGLAND, James [/]; (). COLBY, Edward [/]; (). DAMES, Andrew [/]; (). ENGLAND, James [/]; (). COLBY, Edward [/]; ().	Published	
(54) Title: BIO-ASSAY TECHNIQUE (54) Titre: TECHNIQUE DE BIODOSAGES (57) Abstract <p>The present invention relates to a system for carrying out parallel bioassays. Microfabricated labels (7) are made to each carry a biochemical test, many different labels are mixed together with an analyte sample (8). A device that reads the individual labels isolates the results of the individual tests. The microfabricated labels have a surface layer of anodised metal and are produced by anodising, lithographic patterning and etching steps. Aluminum is the preferred metal.</p> (57) Abrégé <p>L'invention concerne un système pour effectuer des biodosages en parallèle. On crée par micro-usinage des étiquettes (7) dont chacune est destinée à accueillir un test biochimique, puis on mélange plusieurs étiquettes différentes avec un échantillon d'analyte (8). Un dispositif qui lit les étiquettes individuelles isole les résultats des tests individuels. Les étiquettes créées par micro-usinage sont munies en surface d'une couche en métal anodisé fabriquée par anodisation, par dessin des motifs au moyen d'une technique lithographique et par gravure. On utilise de préférence l'aluminium.</p>		

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 7 : B01J 19/00, G06K 19/06, G01N 33/53, C25D 11/04</p>	<p>A3</p>	<p>(11) International Publication Number: WO 00/16893 (43) International Publication Date: 30 March 2000 (30.03.00)</p>
<p>(21) International Application Number: PCT/GB99/03109 (22) International Filing Date: 17 September 1999 (17.09.99) (30) Priority Data: 9820163.5 17 September 1998 (17.09.98) GB (71) Applicant (for all designated States except US): SENTEC LIMITED (GB/GB); Patent Department, Terrington House, 13-15 Hills Road, Cambridge, Cambridgeshire CB2 1GE (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): DAMES, Andrew (GB/GB); 74 de Freville Avenue, Cambridge, Cambridgeshire CB4 1HU (GB). ENGLAND, James (GB/GB); 44A Butt Lane, Milton, Cambridge, Cambridgeshire CB4 6DG (GB). COLBY, Edward (GB/GB); 45 Argyl Road, Cambridge, Cambridgeshire CB1 3LR (GB).</p>		<p>(81) Designated States: AU, CN, IN, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. (88) Date of publication of the international search report: 24 August 2000 (24.08.00)</p>
<p>(54) Title: BIO-ASSAY TECHNIQUE</p> <p>(57) Abstract</p> <p>The present invention relates to a system for carrying out parallel bioassays. Micro-fabricated labels (7) are made to each carry a biochemical test, many different labels are mixed together with an analyte sample (8). A device that reads the individual labels isolates the results of the individual tests. The microfabricated labels have a surface layer of anodised metal and are produced by anodising, lithographic patterning and etching steps. Aluminum is the preferred metal.</p> 		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 99/03109

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B01J19/00 G06K19/06 G01N33/53 C25D11/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01J G06K G01N C25D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 395 300 A (ALCAN INT LTD) 31 October 1990 (1990-10-31) abstract	1-3, 7-13
A	page 4, line 22 - line 30; claims 1, 10, 12, 17-26; figures 3-5; examples 1, 3	20-22
X	US 5 129 974 A (AURENIUS CARL A D) 14 July 1992 (1992-07-14) abstract	1-3, 7, 8, 13, 14
A	column 9, line 42 - line 48 column 13, line 59 - column 14, line 12; figure 11	4
X	DE 24 16 652 A (FLASDIECK DIERK DR) 16 October 1975 (1975-10-16)	1-3, 7-10, 13, 14
A	page 6, paragraph 3 - page 7, paragraph 1; figure 1	4
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

15 May 2000

Date of mailing of the international search report

23.05.00

Name and mailing address of the ISA

European Patent Office, P.O. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Veefkind, V

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 99/03109

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	RIGBY W R ET AL.: "An anodizing process for the production of Inorganic microfiltration membranes" TRANSACTIONS OF THE INSTITUTE OF METAL FINISHING, vol. 68, August 1990 (1990-08), pages 95-98, XP002130485 the whole document	1-3,7-14
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 08, 30 August 1996 (1996-08-30) & JP 08 102544 A (SATO YOICHI), 16 April 1996 (1996-04-16) abstract	1-3
A		4-7
X	GB 2 306 484 A (UNIV HERTFORDSHIRE) 7 May 1997 (1997-05-07) cited in the application page 15, line 12 - line 23	15,18, 19,24,25
Y	page 19, line 24 -page 21, line 2; figure 4	25
A	the whole document	13,14, 20-23
X	WO 97 12680 A (SARGENT BRADLEY J ;IRORI (US); DAVID GARY S (US); NOVA MICHAEL P () 10 April 1997 (1997-04-10)	15,18,19
Y	page 17, line 28 -page 18, line 4 page 37, line 1 - line 20; figure 33 page 148, line 9 - line 28 page 160, line 3 - line 13 page 182, line 9 - line 18 page 35, line 27 -page 36, line 9; figures 19-32 page 76, line 3 -page 77, line 2	25
P,X	WO 99 02266 A (AKZO NOBEL NV ;DAMME HENDRIK SIBOLT VAN (NL); KREUWEL HERMANUS JOH) 21 January 1999 (1999-01-21) page 2, line 21 -page 3, line 8 page 6, line 4 - line 25; claims 1-4	1-3, 7-10,13, 14,20-23
A	LAURELL T ET AL: "ENHANCED ENZYME ACTIVITY IN SILICON INTEGRATED ENZYME REACTORS UTILIZING POROUS SILICON AS THE COUPLING MATRIX" SENSORS AND ACTUATORS B,CH,ELSEVIER SEQUOIA S.A., LAUSANNE, vol. 31, no. 3, 1 March 1996 (1996-03-01), pages 161-165, XP000630913 ISSN: 0925-4005 the whole document	1-3,7-14

-/-

INTERNATIONAL SEARCH REPORT

Int. Search Application No.
PCT/GB 99/03109

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 96 24061 A (ONTOGEN CORP) 8 August 1996 (1996-08-08) cited in the application page 47, line 6 -page 49, line 29; claims 14-53; figure 7</p>	14,20-23

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 99/03109

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-14,16,17,20-23

Claims 1-3,7,8,13,14,16,17,23, related to a solid support with an anodised metal surface layer,
Claims 4-6, related to a method of fabricating such support,
Claims 9-12, related to a method of fabricating such support,
Claims 20-22, related to a process of separating results of many binding experiments.

2. Claims: 15,18,19,24,25

Claims 15,18,19,24,25, related to an optical reader.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03109

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0395300 A	31-10-1990	CA 1337173 A AT 143731 T DE 69028728 D DE 69028728 T DK 395300 T HK 1006039 A JP 2300661 A JP 2993513 B US 5124172 A	03-10-1995 15-10-1996 07-11-1996 06-03-1997 02-12-1996 05-02-1999 12-12-1990 20-12-1999 23-06-1992
US 5129974 A	14-07-1992	NONE	
DE 2416652 A	16-10-1975	NONE	
JP 08102544 A	16-04-1996	NONE	
GB 2306484 A	07-05-1997	AU 696505 B AU 7318496 A CA 2235837 A EP 0863797 A WO 9715390 A	10-09-1998 15-05-1997 01-05-1997 16-09-1998 01-05-1997
WO 9712680 A	10-04-1997	US 5874214 A US 6025129 A US 6017496 A US 5961923 A AU 707444 B AU 5918596 A AU 7257396 A CA 2216645 A CN 1181720 A EP 0822861 A EP 0853497 A JP 11511238 T WO 9636436 A AU 3577997 A WO 9749653 A	23-02-1999 15-02-2000 25-01-2000 05-10-1999 08-07-1999 29-11-1996 28-04-1997 21-11-1996 13-05-1998 11-02-1998 22-07-1998 28-09-1999 21-11-1996 14-01-1998 31-12-1997
WO 9902266 A	21-01-1999	AU 8863298 A EP 0975427 A	08-02-1999 02-02-2000
WO 9624061 A	08-08-1996	AU 5020496 A CA 2186943 A EP 0754302 A JP 9512036 T US 5770455 A	21-08-1996 08-08-1996 22-01-1997 02-12-1997 23-06-1998